

USP™ TAPERED ISO

Technical Data Sheet

Product Name: USP™ Tapered ISO (Manufactured by Atlas or RMax)

Classification: Thermal Insulation, Polyisocyanurate

Product Description: USP™ Tapered ISO is a closed-cell, polyiso-foam core integrally laminated to heavy black (non-asphaltic), fiber-reinforced felt facers. USP™ ISO is also available in 25-psi density formula. USP™ Tapered ISO is manufactured in a tapered profile to attain positive drainage while maintaining the highest thermal efficiency available in a tapered system. Available in 4' x 4' (1.2m x 1.2m) panels only.

Application Method: USP™ Tapered ISO is applied using mechanical fasteners or hot asphalt in hot mop techniques.

HCFC FREE *ZERO* OZONE DEPLETION POTENTIAL

Approvals: Federal Specification HH-I-1972/GEN and HH-I-1972/2 Class 1. This federal specification has been cancelled.

- ASTM C1289, Type II, Class 1
- California State Insulation Quality Standards and Title 25, Foam Flammability Criteria (License #TC 1231).
- IBC, BOCA, ICBO, and SBCCI Sections on Foam Insulation
- CCMC No.12464-L
- Meets CAN/CGSB-51.26-M86, CAN/ULC-S704

Long-Term Thermal Resistance*

	THICKNESS		SLOPE PER		AVERAGE	
	In	mm	foot	30.5 cm	LTTR	RSI
AA	0.5" – 1.0"	12-25	¼"	3 mm	4.5	.79
A	1.0" – 1.5"	25-38	¼"	3 mm	7.5	1.32
B	1.5" – 2.0"	38-50	¼"	3 mm	10.6	1.86
C	2.0" – 2.5"	50-63	¼"	3 mm	13.7	2.41
X	0.5" – 1.5"	12-38	¼"	6 mm	6.0	1.06
Y	1.5" – 2.5"	38-63	¼"	6 mm	12.1	2.13
G	1.0" – 2.0"	25-50	¼"	6 mm	9.0	1.58
H	2.0" – 3.0"	50-76	¼"	6 mm	15.3	2.69
JJ	0.5" – 1.25"	12-32	3/16"	5 mm	5.3	.93
KK	1.25" – 2.0"	32-50	3/16"	5 mm	9.8	1.72
Q	0.5" – 2.5"	12-63	½"	12 mm	9.0	1.58

*Long-term thermal resistance values of the foam were determined in accordance with CAN/ULC S770. All test samples were third-party selected and tested by an accredited materials testing laboratory.

FM Standard 4450/4470 Approval

USP™ ISO is approved for Class 1 insulated steel, wood, concrete and gypsum roof deck construction for both 1-60 and 1-90 Windstorm Classifications (USP™ ISO may be mopped or mechanically fastened to concrete roof deck). Refer to FM Approval Guide for details on specific systems.

UL Standard 1256 Classification

Insulated metal deck construction assemblies – Construction #120 and #123

UL Standard 790 (ASTM E 108) Classification

Class A with most roof membrane systems. See UL Roofing Materials & Systems Directory.

UL Standard 263 Fire Resistance Classification (ASTM E 119)

Some classifications for fire resistance are P225, P230, P259, P508, P510, P514, P519, P701, P710, P713, P717, P718, P719, P720, P722, P723, P924, P725, P727, P728, P729, P730, P732, P801, P814, P815, P818, P819 and P828. See UL Fire Resistance Directory for updated listings.

UL Standard 1897 Uplift Resistance

120 PSF, 150 PSF, 165 PSF, 245 PSF

UL Certified for Canada

UL of Canada

Insulated Roof Deck Assemblies – Construction #34. Meets CAN/ULC-S126-M86, CAN/ULC-S101-M89, CAN/ULC-S107-M87

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative.

U.S. PLY, INC.

A DANNY ADAIR COMPANY

Corporate Headquarters: P.O. Box 11740, Fort Worth, Texas 76110

TOLL-FREE: 866-PUSH-PLY (866) 787-4759 • Local: (817) 413-0103 • Fax: (817) 413-8221

Website: www.usply.com • Email: sales@usply.com

January 2006