

USP™ NVB

USP™ NVB (M)

(NAILABLE VENTING BASE)

Technical Data Sheet

Product Name: USP™ NVB (Nailable Venting Base); USP™ NVB (M)

Classification: Fiberglass Venting Base Sheet; UL Type G2

Product Description: USP™ NVB (Nailable Venting Base)/USP™ NVB (M) is manufactured with a heavyweight, select fiberglass mat designed and constructed to be strong and wrinkle resistant. The glass mat is saturated with a high quality, non-filled asphaltic bitumen and coated on the underside with a ceramic granule to allow for lateral venting. USP™ NVB/USP™ NVB (M) is designed for use as a base sheet for hot mopped, cold applied and torch applied roofing applications where additional venting is desired in specifications requiring an ASTM D-4897 Type II fiberglass venting base sheet.

Application Method: USP™ NVB (Nailable Venting Base) is applied with mechanical fasteners.

Fastening Pattern: Fastening patterns vary according to desired uplift resistance. Always contact the U.S. Ply, Inc. Technical Services department to verify fastening pattern meets desired uplift resistance. Note: The fastening patterns and lay lines are different between USP™ Base Sheet and USP™ Base (M) because of the difference in product width. To avoid confusion, these products should not be mixed.

Approvals: Meets the requirements of ASTM D 4897 Type II. U.S. Ply products are listed or approved with Underwriter's Laboratories (UL) and Factory Mutual (FM). Contact U.S. Ply, Inc. for specific/applicable codes.

Product Data: USP™ NVB (typical)
UL Designation: UL Type G2
Roll Dimensions: 36' x 36" (10.9m x 0.91m)
Area of roll ft²: 1 square (108 ft²).
Weight: 72 lbs/roll (32.7 kg/m²)
Rolls per pallet: 28 per pallet
Lay Lines: 2"

Product Data: USP™ NVB (M) (typical)
UL Designation: UL Type G2
Roll Dimensions: 32'-11" x 39-3/8" (10m x 1m)
Area of roll ft²: 1 square (107.9 ft²)
Weight: 86 lbs/roll (39.0 kg/m²)
Rolls per pallet: 20 per pallet
Lay Lines: 2"; 4"

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative.

U.S. PLY, INC.

A DANNY ADAIR COMPANY

Corporate Headquarters: P.O. Box 11740, Fort Worth, Texas 76110
TOLL-FREE: 866-PUSH-PLY (866) 787-4759 • Local: (817) 413-0103 • Fax: (817) 413-8221
Website: www.usply.com • Email: sales@usply.com

May 2007