

# USP™ WALKBOARD

## Technical Data Sheet

**Product Name:** USP™ WALKBOARD

**Classification:** Walkboard

**Product Description:** USP™ WALKBOARD is a composite adhered modified bitumen sheet consisting of a smooth underside and a granule top side. Each layer is manufactured with a heavyweight polyester mat designed and constructed to be strong, while remaining wrinkle resistant. The USP™ WALKBOARD is available in APP modified bitumen polymer or SBS polymer and asphaltic bitumen for a strong, durable sheet. Designed for use as a designated walkway for built-up and modified bitumen roofs.

**Application Method:** USP™ APP WALKBOARDS are designed to be torch applied. USP™ SBS WALKBOARDS may be mopped or adhered with SBS adhesive.

**Product Data:** USP™ WALKBOARD (typical)

Sheet Size: 36" x 36" +/- 0.7%

Area of sheet ft<sup>2</sup>: 9 sq. ft.

Weight: 18 lbs/sheet (8.1 kg/m<sup>2</sup>)

Sheets per pallet: 100 per pallet

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative.

***U.S. PLY, INC.***

A DANNY ADAIR COMPANY

Corporate Headquarters: P.O. Box 11740, Fort Worth, Texas 76110

TOLL-FREE: 866-PUSH-PLY (866) 787-4759 • Local: (817) 413-0103 • Fax: (817) 413-8221

Website: [www.usply.com](http://www.usply.com) • Email: [sales@usply.com](mailto:sales@usply.com)

January 2006