

MATERIAL SAFETY DATA SHEET

1. PRODUCT and COMPANY IDENTIFICATION

Manufacturer

U.S. PLY, INC.
P.O. Box 11740
Fort Worth, TX 76110

Non Emergency Information

Telephone: U.S. PLY, INC. (866) 787-4759 or (817) 413-0103

Emergency Information

Transportation Emergency Telephone: 1-800-424-9300.

Product Name: DURAFLEX 30 SBS BASE, DURAFLEX 60 SBS BASE, DURAFLEX SBS POLYBASE, DURAFLEX SBS POLYBASE MA, DURAFLEX SEBS POLYBASE, DURAFLEX 190S SBS, DURAFLEX G4S SBS, DURAFLEX 190 SBS, DURAFLEX G4M SBS, DURAFLEX 190FR SBS, DURAFLEX G4FR SBS, DURAFLEX 250S SBS BASE, DURAFLEX 250 SBS, DURAFLEX 250FR SBS, DURAFLEX 250S TG SBS, DURAFLEX 250TG SBS, DURAFLEX 250FRTG SBS, DURAFLEX DUAL SMOOTH SBS, DURAFLEX DUAL CAP FR SBS, DURAFLEX 60TG SBS BASE, DURAFLEX 90TG SBS BASE, DURAFLEX 90HTTG SBS BASE, DURAFLEX X4S TG SBS BASE, DURAFLEX 4HTS TG SBS BASE, DURAFLEX 190S TG SBS, DURAFLEX 190TG SBS, DURAFLEX 190FR TG SBS, DURAFLEX X4M TG SBS, DURAFLEX 4MHT TG SBS, DURAFLEX X4FR TG SBS, DURAFLEX G4FR TG SBS, DURAFLEX 4MFRHT TG SBS, DURAFLEX ALUM, DURAFLEX COPPER, DURAFLEX COLOR SBS, DURASTAR WH SBS, DURASTAR ALM SBS, DURASTAR WH-TG SBS, DURASTAR ALM-TG SBS, RAPIDGRIP READI-BASE, RAPIDGRIP SR-200, RAPIDGRIP SBS SA CAP, RAPIDGRIP SBS SA FR CAP, RAPIDGRIP SBS UNDERLAYMENT, RAPIDGRIP HT METAL UNDERLAYMENT, USP SBS 160M, USP SBS WALKBOARD

Chemical Name: Asphalt Mixture/Roll Roofing

2. COMPOSITION (Information on Ingredients)

Component	CAS No	Weight %
Chemical Name (common names)		
Asphalt	8052-42-4	55 - 85
Calcium Carbonate	1317-65-3	12 - 30
Crystalline Silica (Sand)	14808-60-7	1 - 5
Talc	14807-96-6	0 - 1
Non-Hazardous Ingredients	N/A	12 - 32
See Section 8 of this MSDS for Exposure Guidelines		

3. HAZARDS IDENTIFICATION

Physical Hazards

APPEARANCE AND ODOR: Black sheet in roll form. Surfaces may include roofing granules, slate, sand, talc or film. Slight asphaltic odor.

Under normal use conditions, this product is not expected to create any unusual emergency hazards.

Inhalation of dust from the product may cause temporary irritation and/or congestion. Individuals affected should be moved to fresh air.

Skin irritation may be treated by gently washing affected area with soap and warm water.

Eye irritation may be treated by flushing eyes with large amounts of water. If irritation persists, seek medical attention.

Potential Health Effects

This product contains a small amount of polyaromatic hydrocarbons which have been shown to cause cancer and respiratory damage in laboratory animals. Some asphalts and some asphalt solutions have produced skin cancer in laboratory animals. No association has been established between industrial exposure and cancer. (IRAC*, PART 4, VOLUME 35). Due to size of the particles, minimal exposure to airborne dust is expected.

Exposure Routes

Primary: Inhalation (breathing dust), skin contact and eye contact.

Inhalation: Irritation of the upper respiratory tract may occur. Acute exposure may irritate mucous membranes with tightness in chest, coughing, wheeziness, or congestion.
Chronic exposure to silica may cause limitation of expansion of the chest, emphysema. Chronic exposure to talc may cause cough, pneumoconiosis.

Skin Contact: Temporary irritation (itching) or redness may occur. Contact with molten asphalt can result in burns.

Absorption: Not applicable

Eye Contact: May irritate eyes. Because of its adhesive and temperature features, the molten asphalt contact with eyes may cause physical damage due to adhesive properties as well as burns.

Ingestion: May cause irritation of the digestive system.

Medical Conditions Aggravated by Exposure

Exposure to dust may aggravate pre-existing upper respiratory and lung diseases or conditions.

4. FIRST AID MEASURES

Inhalation: If breathing difficulty is experienced, move to a fresh air place. Drink water to clear throat and blow nose to remove dust. If difficulty persists, seek medical attention.

Skin Contact: Wash gently with soap and warm water. For molten asphalt contact, cool with ice or water. Do not attempt to remove asphalt immediately. Cover with petroleum jelly (Vaseline). Remove the asphalt has softened. If irritation develops, use a delicate cream. If symptoms persist, in case of redness or blistering seek medical attention for burn treatment.

Eye Contact: Do not rub or scratch eyes. Dust particles may cause the eye to be scratched. Bathe eye immediately with a large amount of water for at least 15 minutes. If irritation persists, seek medical attention immediately.

Ingestion: This product is not intended to be ingested. In case of ingestion seek medical attention immediately.

5. FIRE FIGHTING MEASURES

Flash Point: 570°F (299°C) Asphalt Blend Portion

Flammable Limits:

Lower Explosive Limit N/A

Upper Explosive Limit N/A

Auto Ignition: N/A

Extinguishing Media: Foam, CO2, dry chemical or water spray

Special Fire-fighting Procedures: Wear self-contained breathing apparatus (SCBA) and full protective clothing.

Unusual Fire and Explosive Hazards: None

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: N/A

Environmental Precautions: Pick up large pieces of material. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation. These procedures will help to minimize potential exposures.

Clean-up Methods: This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact the local Public Health Department, or the local office of the EPA.

7. HANDLING AND STORAGE

Handling: Use protective equipment as described in Section 8 of this material safety data sheet when handling uncontained material. Avoid direct exposure to very high heat or flame.

Storage: Keep away from heat, sparks or open flame. Store standing upright on end. Material should be kept dry, and protected from the elements. Recommended storage temperature is between 55°F to 95°F (12.7°C to 35°C). Protect from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Read all product instructions before using. Personal protective equipment should include safety eye wear, fire resistant gloves, and long sleeve work clothes to prevent excessive skin contact. No special ventilation systems are required under normal conditions of use in well ventilated areas.

Exposure Guidelines	OSHA	ACGIH
Calcium Carbonate (1317-65-3)	Total Dust: 15 mg/m ³ TWA Respirable Dust: 5 mg/m ³ TWA	Total Dust: 10 mg/m ³ TWA Respirable Dust: 5 mg/m ³ TWA
Crystalline Silica (containing no asbestos) 14808-60-7	Respirable Dust: 0.1 mg/m ³ TWA	Respirable Fraction: 0.1 mg/m ³ TWA
Talc (containing no asbestos) 14807-96-6	Respirable Dust: (Less than 1% crystalline silica) 2 mg/m ³ TWA ('Silicates')	2 mg/m ³ TWA (Particulate matter containing no asbestos and <1% crystalline)
None of the components in this product are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid
 Appearance: Various colors and surfaces. Thin black asphaltic roll roofing.
 Color: Smooth material is black. Mineral material varies in colors.
 Odor: Asphaltic odor
 Specific Gravity: Approximately 1.2 – 1.6 (H2O = 1)
 Boiling Point: over 600°F (315°C)
 Flash Point: over 570°F (299°C)
 Melting Point: over 250°F (121°C)
 Self-Flammability: None Established
 Auto-Flammability: None Established
 pH: N/A
 Vapor Pressure: N/A
 Solubility in Water: Not soluble
 Explosion data: N/A
 VOC: N/A

10. STABILITY AND REACTIVITY

Chemical Stability

This product is a stable material. This product is not reactive.

Incompatibility

This product will react with strong oxidizing agents, reducing agents, strong acids and alkalis.

Hazardous Decomposition

Oxides of carbon (carbon monoxide, carbon dioxide, carbon particles, and hydrocarbons) are derived from burning.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Dust from this product is an irritant and may cause irritation or scratchiness of the throat, and/or itching in the eyes and skin.

Carcinogenicity

There is no data for this product as a whole.

Component Carcinogenicity

Crystalline Silica (14808-60-7) ACGIH: A2 – Suspected Human Carcinogen
 IARC: Group 1 – Carcinogen to Humans (IARC Monograph 68, 1997, inhaled in the form of quartz or cristobalite from occupational sources)

Talc (14807-96-6) ACGIH: A4 – Not Classifiable as a Human Carcinogen
 IARC: Supplement 7, 1987; Monograph 42, 1987 (Group 3 not classifiable)

Additional toxicological Information

This material is in a solid form; therefore, exposures to hazardous dusts or fumes are not expected to occur. Exposure limits are given for reference only.

Asphalt: The International Agency for Research on Cancer (IARC) has stated that studies of workers exposed to asphalt provide inadequate evidence of carcinogenicity. IARC had previously classified asphalt as a Group 3 substance. Animal studies in which high concentrations of asphalt fumes were breathed for extended periods of time did not indicate any cancer effects. Bronchitis and pneumonitis were observed. Two studies where condensed fractions of certain asphalt fume condensates collected for these studies were repeatedly applied to the skin of laboratory animals reported the induction of skin cancers. The asphalt fume condensates collected for these studies were subjected to extremely high temperatures (601°F/316°C) and were heated for seven to ten hours while being continually stirred. This is not typical of any asphalt application. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be generated upon excessive heating, which results in thermal cracking of the asphalt compounds. Some of these PAHs have been identified as having potential carcinogenic and reproductive health effects.

12. ECOLOGICAL INFORMATION

Biodegradation:	Not Established
Chemical degradation:	Not Established
Bioaccumulation:	Not Established
Agility:	Not Established
Ecotoxicity influence on Organisms:	Not Established
Ecotoxicity in water:	Not Established
Other toxicity:	Not Established

13. DISPOSAL CONSIDERATIONS

This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact the local Public Health Department, or the local office of the EPA.

14. TRANSPORTATION INFORMATION

Shipping Information

This product is not classified as a hazardous material for transport.

DOT (Ground): N/A
Hazard Class: N/A
DOT Label: N/A
Air: N/A
Water: N/A
Freight Classification: Roofing composition or prepared roofing.

15. REGULATORY INFORMATION

US Federal Regulations:

There is no regulation on this product as a whole.

SARA Title III:

None of the products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) or CERCLA (40 CFR 302.4).

16. OTHER

NFPA: Fire 1; Health 1; Reactivity 0
HMIS: Flammability 1; Health 1; Reactivity 0

Prepared by:
U.S. PLY, INC. Technical Services Department
P.O. Box 11740
Fort Worth, TX USA 76110

The information and recommendations contained herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information supplied upon the condition that the persons receiving said information will make their own determination as to its suitability for their particular purpose prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, including the merchantability or fitness for a particular purpose are made herein with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. U.S. PLY, Inc. reserves the right to change the design, specification or any other features at any time, without notice, while otherwise maintaining regulatory compliance.

Issue Date: 9/24/04 - Revised Date: 2/22/06 Revision Disclosure: Addition of new products. Change of Address.