

USP™ MINERAL CAP SHEET

Technical Data Sheet

Product Name: USP™ MINERAL CAP SHEET

Classification: Fiberglass BUR Cap Membrane; UL Type G3

Product Description: USP™ Mineral Cap Sheet is manufactured with a heavyweight, select fiberglass mat designed and constructed to be strong and protect against UV, weathering and physical damage. The glass mat is saturated with a high quality, non-filled asphaltic bitumen and coated with a ceramic granule surface for a strong, durable cap sheet. Designed for use as a mineral cap sheet in hot mop applied roofing applications and specifications requiring ASTM D-3909 cap sheet.

Application Method: USP™ Mineral Cap Sheet is applied using hot asphalt in hot mop techniques.

Approvals: Meets the requirements of ASTM D 3909. U.S. Ply products are listed or approved with Underwriter's Laboratories (UL) and Factory Mutual (FM). Contact U.S. Ply, Inc. for specific/applicable codes.

Product Data: USP™ Mineral Cap Sheet (typical)

UL Designation: UL Type G3

Roll Width: 36" +/- 0.7%

Area of roll ft²: 1 squares (108 ft²).

Weight: 72 lbs/roll (32.6 kg/m²)

Rolls per pallet: 28 per pallet (TX) / 30 per pallet West Coast

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative.

U.S. PLY, INC.

A DANNY ADAIR COMPANY

Corporate Headquarters: P.O. Box 11740, Fort Worth, Texas 76110

TOLL-FREE: 866-PUSH-PLY (866) 787-4759 • Local: (817) 413-0103 • Fax: (817) 413-8221

Website: www.usply.com • Email: sales@usply.com

April 2007