



4" MIN.

WOOD NAILER
ATTACHED TO
SUBSTRATE -
OVERALL
THICKNESS TO
MATCH
INSULATION

WALL
ASSEMBLY

RIGID
INSULATION

APPROVED MASTIC OR SEALANT
AT JUNCTION OF MEMBRANE AND
EDGE METAL

SBS SMOOTH MODIFIED BITUMEN
BACKER SHEET REQUIRED IN 15
AND 20 YEAR SYSTEMS ONLY.
SET IN HOT ASPHALT OR
DURAFLEX 954 PREMIUM
FLASHING CEMENT.

SBS MODIFIED BITUMEN
MEMBRANE SET IN HOT ASPHALT
OR DURAFLEX 901 PREMIUM SBS
MODIFIED ADHESIVE

PRIMED METAL EDGE FLASHING,
MIN. 4" FLANGE, SET IN USP #640
STANDARD ROOF CEMENT OR
DURAFLEX 954 PREMIUM SBS
FLASHING CEMENT

SBS MODIFIED BITUMEN
PRE-FLASHING SET IN HOT
ASPHALT OR DURAFLEX 901
PREMIUM SBS MODIFIED
ADHESIVE

FASTENERS 3" O.C. STAGGERED
(TYPICAL)

BASE/PLY SHEET(S)

NOTES:

1. BASE/PLY SHEET(S) TURNED OVER
EDGE AND EXTENDED BELOW
BLOCKING OR A MINIMUM OF 1 1/2"
(38 MM), WHICHEVER IS GREATER.
2. 15 & 20 YEAR DETAIL: SBS SMOOTH
MODIFIED BITUMEN BACKER
SHEET AND SBS GRANULE
SURFACED MODIFIED BITUMEN
MEMBRANE ARE APPLIED OVER
METAL FLANGE.
3. APPROVED MASTIC OR SEALANTS
ARE DURAFLEX 954 PREMIUM SBS
FLASHING CEMENT, PLYLINK
CONSTRUCTION
ADHESIVE/SEALANT, OR LIQUA-PLY
FLASHING.
4. DURAFLEX ALUM MAY BE USED
FOR FLASHING MATERIAL IN LIEU
OF HOT ASPHALT APPLIED SBS
FLASHING MEMBRANE. DURAFLEX
ALUM MAY ONLY BE APPLIED WITH
HOT ASPHALT OR USING THE HEAT
WELDING METHOD OR PLYLINK
FLASH-N-PATCH. DO NOT USE
SOLVENT BASED ADHESIVES TO
INSTALL DURAFLEX ALUM.

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



U.S. PLY, INC.

Pioneered with performance in mind... Engineered to stand the test of time.

TITLE:

SBS PERIMETER FLASHING DETAIL (GRANULATED)

DATE:
05-14-2004

REVISIONS:
01-31-2011

SCALE:
N.T.S.

DF-2