



NOTES:

1. FASTENERS SHALL BE PLACED IN EACH SECTION OF CAP FASCIA IN ACCORDANCE WITH SMACNA REQUIREMENTS AND WIND LOAD REQUIREMENTS.
2. COVER PLATE SHALL BE EMBEDDED IN PLYLINK HP SEALANT OR OTHER APPROVED SEALANT. TWO FASTENERS SHALL BE PLACED AT THE CENTER OF EACH SECTION OF CAP FASCIA AND COVER PLATE. SEAL FASTENERS WITH PLYLINK HP SEALANT OR OTHER APPROVED SEALANT.
3. DURAFLEX ALUM MAY BE USED FOR FLASHING MATERIAL IN LIEU OF HOT ASPHALT APPLIED SBS FLASHING MEMBRANE. DURAFLEX ALUM MAY ONLY BE APPLIED WITH HOT ASPHALT OR USING THE HEAT WELDING METHOD OR PLYLINK FLASH-N-PATCH. DO NOT USE SOLVENT BASED ADHESIVES TO INSTALL DURAFLEX ALUM.

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



U.S. PLY, INC.

Pioneered with performance in mind... Engineered to stand the test of time.

TITLE: **SBS PERIMETER CURB FLASHING DETAIL**

DATE: 05-14-2004	SCALE: N.T.S.
REVISIONS: 01-31-2011	DF-3