



- SHEET-METAL COUNTERFLASHING
- PRIME SURFACE IF REQUIRED
- TOP COAT LIQUA PLY FLASHING OR FINISH
- OPTIONAL TO CAST MATCHING GRANULES IN TOP COAT
- REINFORCING PLY OF USP POLYFORCEMENT OR USP REMAT 100 ENCAPSULATED IN LIQUA-PLY FLASHING BASE COAT
- BASE COAT - LIQUA-PLY FLASHING
- MODIFIED BITUMEN MEMBRANE
- COMPATIBLE SEALANT

- NOTES:**
1. THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL.
  2. DETAIL DEPICTS THE WEATHERPROOFING PROTECTION AND DOES NOT REPRESENT COUNTER FLASHING DESIGN.
  3. FOR ROOF SYSTEMS WITH FACTORY-APPLIED GRANULE SURFACING, PROPERLY PREPARE CAP SHEET TO RECEIVE FLASHING.

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



# U.S. PLY, INC.

*Pioneered with performance in mind... Engineered to stand the test of time.*

TITLE: **LIQUA-PLY FLASHING OF BASE FLASHING AT CONCRETE WALL DETAIL**

DATE: **05-14-2004**

SCALE: **N.T.S.**

REVISIONS: **01-31-2011**

**DFTG-26**