



NOTES:

1. THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN DECK AND PENETRATION.
2. OPTIONAL MATCH GRANULES CAST INTO LIQUA-PLY FLASHING OR LIQUA-PLY FINISH.

PRIME SURFACE IF REQUIRED

TOP COAT - LIQUA-PLY FLASHING OR LIQUA-PLY FINISH

USP POLYFORCEMENT OR USP REMAT 100 TARGET SHEET SET IN AND COVERED WITH LIQUA-PLY FLASHING

APPROX. 6"

USP POLYFORCEMENT OR USP REMAT 100 FINGER WRAP SET IN LIQUA-PLY FLASHING

BASE COAT - LIQUA-PLY FLASHING

MODIFIED BITUMEN MEMBRANE

SEAL AROUND PENETRATION WITH COMPATIBLE SEALANT

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



U.S. PLY, INC.

Pioneered with performance in mind... Engineered to stand the test of time.

TITLE:

LIQUA-PLY FLASHING AT EQUIPMENT SUPPORT STAND LEG

DATE:
05-14-2004

REVISIONS:
01-31-2011

SCALE:
N.T.S.

DFTG-27