

TOP COAT - PLY-FLASH SYSTEM

DRAIN STRAINER

MODIFIED BITUMEN MEMBRANE

BASE COAT - PLY-FLASH SYSTEM

USP POLYFORCEMENT FINGER WRAP SET IN PLY-FLASH SYSTEM - EXTENDED INTO DRAIN BOWL BEYOND CLAMPING RING

USP POLYFORCEMENT TARGET SHEET SET IN AND COVERED WITH PLY-FLASH SYSTEM

CLAMPING RING

CAST-IRON DRAIN BOWL

DECK CLAMP

ROOF DECK PROPERLY SUPPORTED AT DRAINS
ROOF DRAIN HEIGHT FROM DECK MAY VARY

NOTES:

1. THE USE OF A METAL DECK SUMP PAN IS NOT RECOMMENDED. HOWEVER, DRAIN RECEIVER/BEARING PLATES ARE APPLICABLE WITH SOME PROJECTS.
2. THE DESIGNER SHOULD CONSIDER INSULATING THE DRAIN COMPONENTS BELOW THE DECK TO PREVENT POTENTIAL CONDENSATION.
3. OPTIONAL CAST MATCHING GRANULES IN PLY-FLASH SYSTEM.

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



U.S. PLY, INC.

Pioneered with performance in mind... Engineered to stand the test of time.

TITLE:

USP PLY-FLASH SYSTEM AT ROOF DRAIN

DATE:
05-14-2004

SCALE:
N.T.S.

REVISIONS:
01-31-2011

DW-31