



EQUIPMENT FLASHING

8" MINIMUM  
FLASHING HEIGHT

WOOD NAILER  
ATTACHED TO  
SUBSTRATE - OVERALL  
THICKNESS TO MATCH  
INSULATION

FIRE RETARDANT CANT

APP MODIFIED BITUMEN FLASHING  
EXTENDED UP AND OVER TOP OF CURB

WOOD CURB

ROOFTOP EQUIPMENT  
FRAME

SHEET-METAL RECEIVER  
WITH REMOVABLE  
COUNTERFLASHING

GASKETED FASTENERS -  
24" O.C. - MINIMUM TWO  
FASTENERS PER SIDE.

FASTENERS APPROX. 8" O.C.

BASE/PLY SHEET(S) -  
OPTIONAL: EXTENDED  
ABOVE TOP OF CANT

6" MIN.

APP MODIFIED BITUMEN  
MEMBRANE FLASHING  
ADHERED TO APP  
MEMBRANE BACKER

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



**U.S. PLY, INC.**

*Pioneered with performance in mind... Engineered to stand the test of time.*

TITLE:

**APP EQUIPMENT CURB FLASHING DETAIL**

DATE:  
**05-14-2004**

REVISIONS:  
**01-31-2011**

SCALE:  
**N.T.S.**

**DW-6**