

# SAFETY DATA SHEET

**SDS# 1004**

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** USP #41 Standard Asphalt Primer

**CAS #:** Mixture

**Generic Name:** Asphalt Primer, ASTM D 41 Primer, Type II Primer

**Chemical Name:** Organic solvents and additives

**Chemical Family:** N/A

**Recommended Use:** A bond enhancing roof primer. A fast drying asphalt primer for use to surfaces to promote bonding of asphalt roofing materials in various roofing applications.

**Recommended Restrictions:** For exterior use only. Do not use indoors. Adequate ventilation recommended. Not recommended for coal tar pitch roofs.

**Supplier Information:**

U.S. PLY, INC.  
P.O. Box 11740  
Fort Worth, TX 76110  
(866) 787-4759 or (817) 413-0103  
Internet Website: [www.usply.com](http://www.usply.com)  
Email: [technical@usply.com](mailto:technical@usply.com)

**Toll Manufacturer Location:**

American Industrial Manufacturers of  
Building Materials (AIM)  
6505 W. Park Blvd Suite 306-366  
Plano, TX 75093  
(214) 254-4720  
[www.aimbuildingmaterials.com](http://www.aimbuildingmaterials.com)

**Emergency Telephone Number**

Company Phone: (817)-413-0103  
Call Chemtrec Day or Night: 1-800-424-9300

Trade Name: USP® 41 STANDARD ASPHALT PRIMER, (aka AIM100)

## 2. HAZARDS IDENTIFICATION

Physical Hazards:	Flammable liquids	Category 3
Health Hazards:	Specific target organ Toxicity (repeated exposure):	Category 1
Aspiration toxicity:		Category 1
Environmental Hazards:	Not classified	
OSHA Defined Hazards:	This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)	

Label elements:



Signal word:	Appearance Viscous Danger	Physical State: Liquid	Odor: Solvent (Mineral Spirits)
Hazard Statements:	Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Flammable liquid and vapor		
Prevention:	Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Keep away from heat/sparks/open flames/hot surfaces. Keep container tightly closed when product is not in use. Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection		
Response:	Get medical advice/attention if you feel unwell IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction		
Storage:	Store locked up. Store in a well-ventilated place. Keep cool		

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations See section 13 of this SDS for disposal instructions.

Hazards not otherwise classified (HNOC):

n/a

Supplemental Information: Unknown acute toxicity 1.70055% of the mixture consists of ingredient(s) of unknown toxicity  
 • May be harmful in contact with skin  
 • Toxic to aquatic life with long lasting effects

**3. COMPOSITION INFORMATION ON INGREDIENTS**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	Common Name and synonyms	CAS #	Weight - %
Asphalt (at Ambient Temperature)	Asphalt	8052-42-4	60 - 70
Mineral Spirits (with < 0.1% Benzene)	Mineral Spirits	8052-41-3	30-40
Nonane		111-84-2	0-10
Trimethyl Benzene (mixed Isomers)		23331-13-7	0-10
Non Hazardous Ingredients		NE	NE
NE = Not Established			

**4. FIRST AID MEASURES**

General Advice: Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Inhalation: Move victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur.

Skin Contact: Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation occurs: Get medical advice/attention.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Aspiration may cause pulmonary edema and pneumonitis. If ingestion of a large amount does occur, call a poison control center immediately.

Self-protection of first aider: Pay attention to self-protection!

Most important symptoms /effects, acute and delayed indication of immediate medical and special treatment needed:

In case of shortness of breath, give oxygen. Symptoms may be delayed. May cause eye and skin irritation.

General information: IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Physicians note: Treat symptomatically.

**5. FIRE FIGHTING MEASURES**

Suitable extinguishing media: Dry chemical, dry powder, CO2 or sand. Use foam or water fog as a last resort.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Sealed container may rupture/burst when heated or exposed to excessive heat.

Hazardous combustion products: Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosive data:

Sensitivity to Mechanical Impact: Not Sensitive

Sensitivity to Static Discharge: May be ignited by heat, sparks, or flames.

Special protective equipment and precautions for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural fire-fighters protective clothing will only provide limited protection.

Fire-fighting

Equipment instructions:

In case of fire and/or explosion do not breathe fumes. Fire-fighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.

Specific methods:

In the event of fire, cool tanks with water spray. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures:

Remove sources of ignition. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Use personal protection recommended in Section 8.

Methods and materials for containment and cleaning up:

Dike far ahead of spill for later disposal. Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite followed with plastic sheet to minimize spreading or contact with rain. Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13). Prevent product from entering drains. Never return spills in original containers for re-use. Clean contaminated objects and areas thoroughly observing environmental regulations.

Environmental precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional ecological information.

**7. HANDLING AND STORAGE**

Precautions for safe handling:

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities:

The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage. Incompatible with strong acids and strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Read all product instructions before using. No ACGIH or OSHA PEL is assigned to this mixture.

. Exposure limits for the component materials are shown below.

. This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA.

Components	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt (CAS 8-52-42-4)	TWA: 0.5 mg/m3 benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m3 fume 15 min.
Mineral Spirits (with < 0.1% Benzene) (CAS 8-52-41-3)	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m3 (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m3	IDLH: 20000 mg/m3 Ceiling: 1800 mg/m3 15 min TWA: 350 mg/m3
Nonane (CAS 111-84-2)	TWA: 200 ppm	(vacated) TWA: 200 ppm (vacated) TWA: 1050 mg/m3	TWA: 200 ppm TWA: 1050 mg/m3
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m3	-

Biological limit values: No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls: Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of solvent vapors. Ventilation must be sufficient to maintain solvent vapor concentrations below the TWA limits outlined above.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Wear safety glasses with side shields (or goggles) are recommended.  
Hand protection: Wear protective gloves and protective clothing that is resistant to chemical penetration.  
Skin protection: Wear protective gloves and protective clothing that is resistant to chemical penetration.  
Respiratory protection: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Thermal hazards: n/a

General hygiene considerations:

When using do not smoke. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance  
Physical State: Liquid  
Form: Viscous  
Color: Black  
Odor: Solvent (mineral spirits) and asphaltic odor.  
Odor threshold: 1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.  
pH: n/a  
Melting point: n/a  
Freezing point: -94°F (-70°C)  
Boiling point: > 310°F (154°C)  
Flash point: > 105.0°F (40.5°C) Setflash  
Evaporation rate: 0.1 Butyl acetate = 1  
Flammability  
(solid, gas): n/a  
Flammability Limits:  
Lower/upper %: 1.6/7.0  
Explosive Properties: Vapor accumulation could flash or explode if ignited.  
Oxidizing Properties: None  
Vapor Pressure: 0.3 (kPa) @ 20°C  
Vapor Density: 5.3 where: air = 1 @ 20°C  
Solubility in Water: Insoluble  
Solubility in other solvents: Soluble in aromatic and aliphatic solvents.  
Partition coefficient  
(n-octanol/water): n/a  
Auto-ignition temp: 626°F (330°C)  
Decomposition temp: n/a  
Kinematic Viscosity: n/a  
Dynamic Viscosity: n/a  
Softening Point: n/a  
Molecular Weight: n/a  
VOC Content (%): < 350 g/l  
Density: 8.2 – 8.4 lbs/gal  
Volatile %: 20 – 30%  
Specific gravity: 0.98

## 10. STABILITY AND REACTIVITY

Reactivity: n/a  
Chemical Stability: This product is stable under normal temperature conditions.  
Possible hazardous reactions: Hazardous polymerization will not occur.  
Conditions to avoid: Heat, flames and sparks.  
Incompatible materials: Strong acids and strong oxidizing agents.  
Hazardous decomposition Products: Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiates.

## 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

# U.S. PLY, INC.

SDS # 1004

Product Information: Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingestion: If swallowed, do not induce vomiting. Get medical attention immediately. However, ingestion is not likely to be a primary route of occupational exposure.

Inhalation: Avoid breathing vapors or mists. May cause irritation to the respiratory system. However, this product does not currently meet the criteria for classification.

Skin contact: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact: Avoid contact with eyes. Causes eye irritation.

USP 41 Standard Asphalt Primer (CAS Mixture) aka AIM100.

Component	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) (CAS 8-52-42-4)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Nonane (CAS 111-84-2)	-	-	= 3200 ppm (Rat) 4h
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)	= 8970 mg/kg (Rat)	-	-

\* Estimates for product may be based on additional component data not shown.

Information on toxicological effects:

Symptoms: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Skin corrosion/irritation: Can cause skin irritation.

Serious eye damage

/eye irritation:

Not classified. Contact with eyes may cause physical damage due as well as severe irritation and pain.

Corrosivity:

Not classified.

Respiratory sensitization:

May cause sensitization of susceptible persons.

Skin sensitization:

Irritating to skin.

Germ cell mutagenicity:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity:

The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

**IARC Monographs, Overall Evaluation of Carcinogenicity**

Component Name	ACGIH	IARC	NTP	OSHA (29 CFR 1910.1001-1050)
Asphalt at ambient temperature (CAS 8052-42-4)	-	2B	-	-
Mineral Spirits (CAS 8052-41-3)	-	3	-	-

  

Legend		Legend	
ACGIH (American Conference of Governmental Industrial Hygienists)		IARC (International Agency for Research on Cancer)	
A1	Known Human Carcinogen	Group 1	Carcinogenic to Humans
A2	Suspected Human Carcinogen	Group 2A	Probably Carcinogenic to Humans
A3	Animal Carcinogen	Group 2B	Possibly Carcinogenic to Humans
A4	Not Classified as a Human Carcinogen	Group 3	Not Classifiable as a Human Carcinogen

  

NTP (National Toxicology Program)		OSHA (Occupational Safety and Health Administration of the US Department of Labor)	
Known	Known Carcinogen	X	Present
Reasonably Anticipated	Reasonably Anticipated to be a Human Carcinogen		

Component Information: \* The IARC Monograph (Vol. 103, 2013, Bitumen and Bitumen Emissions) defines Asphalt as "Group 2B, Possible Carcinogen to Humans". This definition is based on studies of exposure to Asphalt fumes at elevated temperatures. The Monograph states that temperature plays an important role in determining the degree of exposure and also the carcinogenic potential of bitumen emissions. This same Monograph states that Asphalt is non-volatile at ambient temperature. There is no data presented in the Monograph to demonstrate that Asphalt at ambient temperature is considered a carcinogen. Since the normal use of this product is at ambient temperature, the Asphalt used in this product is not listed as a carcinogen. No other national or international agency has defined Asphalt as a carcinogen.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity: n/a

- Single exposure: n/a

- Repeated exposure: n/a

Aspiration hazard: not classified

Chronic effects: Not expected to be hazardous by OSHA criteria.

Further information: Symptoms may be delayed.

Numerical measures of toxicity – No information available

The following values are calculated based on chapter 3.1 of the GHS document. For exterior use only. Do not use indoors.

ATEmix (oral) 7,970.00  
 ATEmix (dermal) 3,218.00

**12. ECOLOGICAL INFORMATION**

Ecotoxicity: Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is expected. Not expected to be harmful to aquatic organisms.

Component	Algae/aquatic plants	Fish	Crustacea
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)	-	7.72; 96 h Pimephales promelas mg/L LC50 flow-through	-
* Estimates for product may be based on additional component data not shown.			

Persistence and degradability: n/a  
 Bioaccumulation potential: n/a  
 Partition coefficient:  
 Asphalt (CAS 8052-42-4)  
 (at ambient temperature): 6  
 Mobility in soil: n/a  
 Other adverse effects: n/a

**13. DISPOSAL CONSIDERATIONS**

Disposal instructions: Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.  
 Hazardous waste code: D001: Waste flammable material with a flash point >105°F.  
 Waste from residues /unused products: Dispose of in accordance with local regulations.  
 Contaminated packaging: Do not reuse container.

**14. TRANSPORTATION INFORMATION**

**DOT** Regulated  
 DOT Ground: Not regulated if shipped by ground in quantities LESS than 119 gallons (450 L)  
 DOT Ground: Regulated if shipped by ground in quantities GREATER than 119 gallons (450 L)  
 UN number: UN1993  
 UN proper shipping name: Combustible liquid, n.o.s (mineral spirits)  
 Transport Hazard Class: 3, Combustible liquid  
 Packing Group: III

**IATA** Regulated  
 UN number: UN1993  
 UN proper shipping name: Combustible liquid, n.o.s (mineral spirits)  
 Transport Hazard Class: 3, Combustible liquid  
 Packing Group: III

**IMDG** Regulated  
 UN number: UN1993  
 UN proper shipping name: Tars, liquid  
 Transport Hazard Class: 3, Combustible liquid  
 Packing Group: III

**DOT**



IATA; IMDG



Further Information: If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in quantities less than 7.9 gallons (30 L), IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

**15. REGULATORY INFORMATION****US Federal Regulations:****SARA 311/312**

Hazard Categories:

Acute health hazard:	Yes
Chronic health hazard:	Yes
Fire hazard:	Yes
Sudden pressure:	No
Reactive hazard:	No

**SARA 313 (TRI reporting):** Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**CWA (Clean Water Act):** This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERLA Hazardous Substance List (40 CFR 1910.1001-1050):**

Asphalt (CAS 8052-42-4) Listed

**Other federal regulations:****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:**

Not regulated

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

Not regulated

**Safe Drinking Water Act:****(SDWA)**

Not regulated

**US State Regulations:** **WARNING:** This product contains a chemical known to the State of California to cause cancer.

**US. Massachusetts RTK - Substance List**

Asphalt (CAS 8052-42-4)  
Mineral Spirits (CAS 8052-41-3)  
Nonane (CAS 111-84-2)  
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Asphalt (CAS 8052-42-4)  
Mineral Spirits (CAS 8052-41-3)  
Nonane (CAS 111-84-2)  
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)

**US. Pennsylvania RTK - Hazardous Substances**

Asphalt (CAS 8052-42-4)  
Mineral Spirits (CAS 8052-41-3)  
Nonane (CAS 111-84-2)  
Trimethyl Benzene (mixed Isomers) (CAS 25551-13-7)

**US. Rhode Island RTK**

Not regulated

**US. California Proposition 65****US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Asphalt (CAS 8052-42-4) Listed: January 1, 1990

**US EPA Label Information**

EPA Pesticide Registration: n/a

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health Hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health Hazards 2	Flammability 2	Physical Hazards 0	Personal Protection -
<i>Chronic Hazard Star Legend</i>		<i>* = Chronic Health Hazard</i>		

Issue Date: 5/22/2015 SDS Format  
 Last Revision Date: 3/01/2011 MSDS Format  
 Original Issue Date: 9/24/2004 MSDS Format  
 Revision Disclosure: 3/01/2011 - Addition of new products. 5/22/2015 Change to SDS Format and separation by individual product.

Prepared by:  
 U.S. PLY, INC. Technical Services Department  
 P.O. Box 11740  
 Fort Worth, TX USA 76110

The information and recommendations provided in this Safety Data Sheet are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information supplied upon the condition that the persons receiving said information will make their own determination as to its suitability for their particular purpose prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, including the merchantability or fitness for a particular purpose are made herein with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. U.S. PLY, Inc. reserves the right to change the design, specification or any other features at any time, without notice, while otherwise maintaining regulatory compliance.

End of Safety Data Sheet