



PLYFAST® TERMINATION BAR

Description: PLYFAST® Termination Bars come in variety of sizes, thicknesses, and styles and are made from specially extruded aluminum without any sharp edges.

PlyFast® TB-50: Has a one-inch face with an upper and lower inverted ledge for optimal pressure on membrane when properly secured. Thickness is .050". Comes with holes spaced on 6", 8" or 12" on centers.

PlyFast® TB-75: Has a three-quarter inch face with an upper sealant ledge. Thickness is .075". Comes with holes spaced on 6", 8" or 12" on centers.

PlyFast® TB-90: Has a one-inch face and is flat with no ledges for sealant. Thickness is .090". Comes with holes spaced on 6", 8" or 12" on centers.

PlyFast® TB-100: Has a three-quarter inch face with an upper sealant ledge. Thickness is .125". Comes with holes spaced on 6", 8" or 12" on centers.

PlyFast® TB-125: Has a one-inch face and is flat with no ledges for sealant. Thickness is .090". Comes with holes spaced on 6", 8" or 12" on centers.

Product Data: PLYFAST® Termination Bar (typical)

Product	Thickness	Dimensions	Hole Size	Holes on Center	Pieces/Tube	Weight/Tube
TB-50-6	.050"	1" x 10'	1/4" x 3/8"	6"	50	45 lbs
TB-50-8	.050"	1" x 10'	1/4" x 3/8"	8"	50	45 lbs
TB-50-12	.050"	1" x 10'	1/4" x 3/8"	12"	50	45 lbs
TB-75-6	.075"	1" x 10'	1/4" x 3/8"	6"	50	51 lbs
TB-75-8	.075"	1" x 10'	1/4" x 3/8"	8"	50	51 lbs
TB-75-12	.075"	1" x 10'	1/4" x 3/8"	12"	50	51 lbs
TB-90-6	.090"	1" x 10'	1/4" x 3/8"	6"	50	57 lbs
TB-90-8	.090"	1" x 10'	1/4" x 3/8"	8"	50	57 lbs
TB-90-12	.090"	1" x 10'	1/4" x 3/8"	12"	50	57 lbs
TB-100-6	.100"	1" x 10'	1/4" x 3/8"	6"	50	68 lbs
TB-100-8	.100"	1" x 10'	1/4" x 3/8"	8"	50	68 lbs
TB-100-12	.100"	1" x 10'	1/4" x 3/8"	12"	50	68 lbs
TB-125-6	.125"	1" x 10'	1/4" x 3/8"	6"	50	78 lbs
TB-125-8	.125"	1" x 10'	1/4" x 3/8"	8"	50	78 lbs
TB-125-12	.125"	1" x 10'	1/4" x 3/8"	12"	50	78 lbs

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



PROUDLY
MADE IN THE U.S.A.

CORPORATE HEADQUARTERS: P.O. BOX 1182, BRIDGEPORT, TEXAS 76426

PHONE: (817)413-0103 FAX: (817)413-8221

WWW.USPLY.COM

REV MAY 2023