

USP® TUFFCAP 190S APP

STANDARD MODIFIED BITUMEN MEMBRANE
Product Data Sheet

"PIONEERED WITH PERFORMANCE IN MIND...
ENGINEERED TO STAND THE TEST OF TIME."

USP® TUFFCAP 190S APP is a tough smooth surfaced, APP (Atactic Polypropylene) torch applied membrane. Manufactured with a non-woven polyester mat, that is saturated and coated with high quality, non-blown asphaltic bitumen and APP resins for a durable, heat resistant, flexible and easily maintainable membrane. It is designed for use as a base, inter-ply or cap membrane in modified bitumen roof systems.



Product Name: USP® TuffCap 190S APP	Thickness: 3.5 mm (140 mils)
Classification: Meets ASTM D 6222 Type I, Grade S, APP Modified Bitumen	Weight: 84 lbs/roll (38 kg/m ²)
Application Method: Applied using torch welding techniques.	Roll Dimensions: 39 3/8" x 32' 9" (1m x 10m).

Each roll is approximately 1 square applied.

Physical Properties (ASTM D5147):	Test Results	ASTM D6222 Minimum Standard
Tensile Strength (lbf/in), 0°F (MD/XMD)	98/72 lbf/in	60 lbf/in
Tensile Strength (lbf/in), 73°F (MD/XMD)	69/61 lbf/in	50 lbf/in
Elongation (% @ Max Load), 0°F, (MD/XMD)	11/11%	10%
Elongation (% @ Max Load), 73°F (MD/XMD)	56/56%	23%
Elongation (% @ 5% Max Load), 73°F (MD/XMD)	62/62%	30%
Tear Strength (lbf), (MD/XMD), 73°F, minimum	110/91 lbf	70 lbf
Low Temperature Flexibility, (°F), maximum	pass	32°F
Dimensional Stability, %, maximum	<0.5%	1%
High Temperature Stability, (°F)	pass	230°F
Water Absorption, %, maximum	pass	<3.2%
Moisture Content, %, maximum	pass	<1%

Approvals: UL Classified with Underwriter's Laboratories (UL), is Factory Mutual (FM) Approved, and listed with Florida Building Code (FBC) FL-14405, Texas Department of Insurance (TDI) RC-123, and is Miami-Dade County Approved. Contact U.S. Ply, Inc. for specific/applicable codes.

TEXAS MADE ... TEXAS TUFF



Green Standards Information: USP® TuffCap 190S APP contains approximately 4.0% of recycled materials by product weight. Materials are comprised of post-consumer recycled materials. The post-consumer recycled materials are derived from recycled post-consumer plastics which averts disposal in landfills or commercial dumps.

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



**PROUDLY
MADE IN THE U.S.A.
BY U.S. PLY, INC.**

CORPORATE HEADQUARTERS: P.O. BOX 1182, BRIDGEPORT, TEXAS 76426

PHONE: (817)413-0103 FAX: (817)413-8221

WWW.USPLY.COM

REV MAY 2023