



PLYFAST® MEMBRANE PLATES

Description: PlyFast® Membrane Plates are available in 3 styles to meet all of your single ply membrane fastening needs.

PlyFast® 2.4” Barbed Plate is a round plate, made of 20 gauge Galvalume™ plated metal with a unique, concave circular design with reinforcing ribs and barbs, low profile and a 2.4-inch diameter to assure proper compression of membrane to insulation. Designed for use with the Phillips truss head fastener.

PlyFast® 2” Barbed Plate is a round plate made of 26 gauge Galvalume™ plated metal with a unique, concave circular design with reinforcing ribs and barbs, low profile and a 2-inch diameter to accommodate membrane compression to insulation. Designed for use with the Phillips truss head fastener.

PlyFast® 2” Seam Plate is a round plate made of 25 gauge Galvalume™ plated metal with a unique, concave circular design with reinforcing ribs and low profile and a 2-inch diameter to accommodate membrane compression to insulation. Designed for use with the Phillips truss head fastener.

Corrosion Coating: Corrosion resistant coating exhibits less than 15% red rust which meets or exceeds FM 4470 corrosion standards and withstands 30 cycles of the Kesternich DIN 50018 SFW 2.0 test.

Approvals: PlyFast® Membrane Plates are listed or approved with Factory Mutual (FM). Contact U.S. Ply, Inc. for specific/applicable codes.

Fastening Pattern: Consult U.S. Ply Technical Department and/or Factory Mutual requirements for recommended patterns in normal, exposed, and high wind velocity areas.

Product Data: PLYFAST® Membrane Plates Ordering Information (typical)

| Product | Pieces/Box | Weight/Box |
|-------------------------------|------------|------------|
| PlyFast® 2.4” Barbed Plate-D | 1000 | 36 lbs |
| PlyFast® 2.4” Barbed Plate-T | 1000 | 52 lbs |
| PlyFast® 2” Barbed Plate-D | 1000 | 34 lbs |
| PlyFast® 2” Barbed Plate - T | 1000 | 28 lbs |
| PlyFast® 2” Seam Plate-D | 1000 | 29 lbs |
| PlyFast® PI 2” Seam Plate - T | 1000 | 27 lbs |

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by “in-house” and independent “third party” evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer’s representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



CORPORATE HEADQUARTERS: P.O. BOX 11740, FORT WORTH, TEXAS 76110

**TOLL-FREE: 866-PUSH-PLY (866) 787-4759
LOCAL: (817) 413-0103 • FAX: (817) 413-8221
WWW.USPLY.COM**