



EQUIPMENT FLASHING

8" MINIMUM
FLASHING HEIGHT

WOOD NAILER
ATTACHED TO
SUBSTRATE - OVERALL
THICKNESS TO MATCH
INSULATION

FIRE RETARDANT CANT

SBS MODIFIED BITUMEN MEMBRANE
EXTENDED UP AND OVER TOP OF CURB

WOOD CURB

ROOFTOP EQUIPMENT
FRAME

SHEET-METAL RECEIVER
WITH REMOVABLE
COUNTERFLASHING

GASKETED FASTENERS -
24" O.C. - MINIMUM TWO
FASTENERS PER SIDE.

FASTENERS APPROX. 8" O.C.

BASE/PLY SHEET(S) -
OPTIONAL: EXTENDED
ABOVE TOP OF CANT

6" MIN

SBS MODIFIED BITUMEN
BASE FLASHING

This detail is furnished "as is" and "as available" and for information only and as a guide for use in conjunction with U.S. Ply products with applicable construction conditions. All dimensions shown are sheet specific; do not scale off of drawing. All details must be checked by the user's designer, architect or engineer to ensure that design is adequate for intended use. Any alterations made to this detail become the design of the user and shall neither be assumed nor construed as U.S. Ply's design. U.S. Ply will not be liable for damages of any kind arising from the use of this website, and/or details, including direct, indirect, incidental, consequential and punitive damages.



U.S. PLY, INC.

Pioneered with performance in mind... Engineered to stand the test of time.

TITLE:

SBS EQUIPMENT CURB FLASHING DETAIL

DATE:
05-14-2004

REVISIONS:
01-31-2011

SCALE:
N.T.S.

DFTG-6