



# DuraWeld® 4M APP ULTRA WHITE

## PRODUCT DATA SHEET

**DuraWeld® 4M APP** is a durable granule surfaced, premium APP (Atactic-Polypropylene) torch applied membrane with a high reflective white granule. Manufactured with a strong non-woven polyester mat that is saturated and coated with a premium quality, non-blown asphaltic bitumen and APP resins for a durable, heat resistant, flexible and easily maintainable membrane. It is designed for use as a cap sheet in modified bitumen roof systems.

Physical Properties (ASTM D5147):	Test Results	ASTM D6 222 Minimum Standard
Tensile Strength (lbf/in), 0°F (MD/XMD)	135/115 lbf/in	60 lbf/in
Tensile Strength (lbf/in), 73°F (MD/XMD)	114/85 lbf/in	50 lbf/in
Elongation (% @ Max Load), 0°F, (MD/XMD)	52/56%	10%
Elongation (% @ Max Load), 73°F (MD/XMD)	47/47%	23%
Elongation (% @ 5% Max Load), 73°F (MD/XM)	52/53%	30%
Tear Strength (lbf), (MD/XMD), 73°F, minimum	134/122 lbf	70 lbf
Low Temperature Flexibility, (°F), maximum	32°F (0°C)	32°F
Dimensional Stability, %, maximum	<0.5%	1%
High Temperature Stability, (°F)	230°F (110°C)	230°F
Water Absorption, %, maximum	pass	<3.2%
Moisture Content, %, maximum	pass	<1%
Granule Embedment, g, maximum	<1.5 g	<2.0 g
<b>Solar Reflectance Information:</b>	<b>Initial</b>	<b>Weathered</b>
Solar Reflectance	0.83	0.55
Thermal Emittance	0.90	0.91
Solar Reflectance Index	104	65
CRRC Rated Product ID	0872-0010	



**Product Data:** DuraWeld® 4M APP (typical)

**Thickness:** 4.1 mm (161 mils)

**Weight:** 100 lbs/roll (45kg/m<sup>2</sup>)

**Roll Dimensions:** 39 3/8" x 32'9" (1mx10m)

Each roll is approximately 1 square applied

**Green Standards Information:** DuraWeld® 4M APP contains approximately 3.2% of recycled materials by product weight. Materials are comprised of post-consumer recycled materials. The post-consumer recycled materials are derived from recycled post-consumer plastics which averts disposal in landfills or commercial dumps

**DISCLAIMER:** U.S. Ply warrants that, at the time of delivery, the U.S. Ply Material delivered shall conform to seller's specifications therefor free and clear of all liens and encumbrances. THIS WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, and of any other obligations or liability on the part of U.S. PLY whether any claim against it is based upon STRICT LIABILITY, NEGLIGENCE, BREACH OF WARRANTY OR ANY OTHER THEORY OR CAUSE OF ACTION. In no event shall U.S. Ply be liable for CONSEQUENTIAL OR INCIDENTAL DAMAGES of any kind, including but not limited to interior damage. Recommendations made by U.S. Ply are believed to be reliable, but U.S. Ply makes no warranty of results to be obtained. If any of the U.S. Ply material fails to conform to the foregoing warranty, SELLER'S SOLE AND EXCLUSIVE REMEDY shall be the replacement of such non-conforming material, provided that such material has been handled and installed in accordance with seller's published handling procedures and installation specifications. This warranty does not apply to, and seller shall not be liable for, labor costs or any other damages resulting from improper or faulty installation of material. The Seller shall also not be liable for labor costs or any other damages resulting from failure of the material itself. Regardless of the theory on which a claim may be made including, without limitation, negligence, contract, breach of warranty, strict liability in tort, misrepresentation, or otherwise, with respect to material delivered or for failure to deliver any material, no claims of any kind whatsoever shall be greater in amount than the purchase price of the material in respect of which damages are claimed. In NO event shall U.S. Ply be liable for INCIDENTAL, CONSEQUENTIAL, SPECIAL, INDIRECT OR PUNITIVE DAMAGES

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**Product Name:** DuraWeld® 4M APP

**Color:** Ultra White

**Classification:** ASTM D 6222 Type I, Grade G. APP Modified Bitumen

**Method:** Torch Welding Techniques

**Approvals:** UL Classified with Underwriter's Laboratories (UL), is Factory Mutual (FM) Approved, and listed with Florida Building Code (FBC) FL-14405, Texas Department of Insurance (TDI) RC-123 and is Miami-Dade County Approved. Contact U.S. Ply, Inc. for specific/applicable codes.



**PROUDLY  
MADE IN THE U.S.A.  
BY U.S. PLY, INC.**

**CORPORATE HEADQUARTERS: P.O. BOX 1182, BRIDGEPORT, TEXAS 76426**

**PHONE: (817)413-0103 FAX: (817)413-8221**

REV MAY 2023

**WWW.USPLY.COM**