



# DuraFlex® 190TG SBS

## PRODUCT DATA SHEET

**DuraFlex® 190TG SBS** is a granule surfaced, premium SBS (Styrene-Butadiene-Styrene) torch applied membrane. Manufactured with a non-woven polyester mat and fiberglass strands for enhanced dimensional stability, high tear strength and puncture resistance. It is saturated and coated with high quality, asphaltic bitumen and SBS elastomers for a durable, flexible and easily maintainable membrane. Designed for use as a cap sheet in modified bitumen torch applied SBS roof systems.

Physical Properties (ASTM D5147):	Test Results	ASTM D6164 Minimum Standard
Tensile Strength (lbf/in), 0°F (MD/XMD)	135/120 lbf/in	70 lbf/in
Tensile Strength (lbf/in), 73°F (MD/XMD)	98/89 lbf/in	50 lbf/in
Elongation (% @ Max Load), 0°F, (MD/XMD)	49/48 %	20%
Elongation (% @ Max Load), 73°F (MD/XMD)	54/60 %	35%
Elongation (% @ 5% Max Load), 73°F (MD/XMD)	62/68 %	38%
Tear Strength (lbf), (MD/XMD), 73°F, minimum	129/117 lbf	55 lbf
Low Temperature Flexibility, (°F), maximum	0°F (-18°C)	0°F
Dimensional Stability, %, maximum	<0.2%	1%
High Temperature Stability, (°F)	250°F (121°C)	215°F
Granule Embedment, g/m <sup>2</sup> avg. loss	1.9	<2 g

**Product Data:** DuraFlex® 190TG SBS (typical)

**Thickness:** 3.8 mm (150mils)

**Weight:** 105 lbs/roll (48 kg/m<sup>2</sup>)

**Roll Dimensions:** 39 3/8" x 32' 9" (1m x 10m)

Each roll is approximately 1 square

**Product Name:** DuraFlex® 190TG SBS

**Classification:** Meets ASTM D 6164 Type I, Grade G. SBS Modified Bitumen Base Sheet

**Application Method:** Applied using torch welding techniques

**Approvals:** UL Classified with Underwriter's Laboratories (UL), is Factory Mutual (FM) Approved, and listed with Texas Department of Insurance (TDI) RC-123. Contact U.S. Ply, Inc. for specific/applicable codes.



**Green Standards Information:** DuraFlex® 190TG SBS contains approximately 2.4% of recycled materials by product weight. Materials are comprised of post-consumer recycled materials. The post-consumer recycled materials are derived from recycled post-consumer plastics which averts disposal in landfills or commercial dumps.

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



**PROUDLY**  
MADE IN THE U.S.A.  
BY U.S. PLY, INC.

**CORPORATE HEADQUARTERS:** P.O. BOX 1182, BRIDGEPORT, TEXAS 76426

**PHONE:** (817)413-0103 **FAX:** (817)413-8221

REV MAY 2023

**WWW.USPLY.COM**