



OlyBond500[®] Green

INSULATION
ADHESIVE

OlyBond500[®] Green provides all the ease and performance of OlyBond500[®] while satisfying important environmental considerations.

It IS Easy Being Green



*Specify Green today,
for tomorrow.*



- Plant-based formula uses rapidly renewable resources in its composition
- Low VOC; no noxious odors
- Contributes to LEED[®] specified projects
- Carries same FM approvals as OlyBond500
- Environmentally sensitive packaging
- Available for both **Bag-in-Box** and **SpotShot** applications



ROOFING PRODUCTS

FASTENERS ADHESIVES DRAINS PIPE SUPPORTS



Not Just Environmentally Friendly—User Friendly, Too

OlyBond500 Green is a dual-component polyurethane adhesive that can be easily applied using our innovative PaceCart 2® dispenser or lightweight SpotShot applicator. With a plant-based formula and low VOCs, it is the ideal choice for LEED specified projects.



Uses

OlyBond500 Green can be used to adhere a variety of insulation and cover boards to a wide selection of roof substrates in both new and re-roof applications. It is also an excellent choice for adhering multiple layers of insulation board and cover board. For more details, refer to Technical Data Sheet.

Application

OlyBond500 Green is dispensed in a semi-liquid band that spreads to several inches while rising ¾–1 inch above the substrate. The insulation/cover board is placed into the adhesive and walked into place. A chemical cure occurs in approximately 4–8 minutes depending on temperature and weather conditions.

Approvals

OlyBond500 Green is approved for use by most roof system manufacturers and is Factory Mutual, Florida Building Code and Miami-Dade approved.



Florida Building Code

Product Data

DESCRIPTION	TEMPERATURE	AMOUNT/PACKAGE	WT/BOX	QTY/CASE	QTY/SKID	COVERAGE RATE/SET (@ 12 IN. O.C.)
OlyBond500 GREEN						
Part 1 Green	40°F +	5 gallons	51.6 lbs	n/a	32	N/A
Part 2 Green—Regular	60°–90°F	5 gallons	42.7 lbs	n/a	32	10–20 Squares/Set
Part 2 Green—Summer	90°F +	5 gallons	42.7 lbs	n/a	32	10–20 Squares/Set
Part 2 Green—Winter	40°–60°F	5 gallons	42.7 lbs	n/a	32	10–20 Squares/Set
OlyBond500 GREEN SpotShot						
Green SpotShot	40°F +	1500 ml cartridges	19.0 lbs	4	40	4–6 Squares/Case

*Coverage rates vary depending on substrate and application. Refer to Technical Data Sheet for details.



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001
800-633-3800 WWW.OLYFAST.COM INFO@OLYFAST.COM

OlyBond® and PaceCart 2® are trademarks of OMG, Inc. Copyright © 2009 OMG, Inc. All rights reserved. 'LEED' and the USGBC logo are trademarks of the U.S. Green Building Council. Used with permission.

LEGAL NOTICE: The OMG Bag-in-Box PaceCart 2® dispensing system incorporates numerous inventive features. Patent protection is pending for many of these features, including the adhesive packaging, the mobile dispensing cart and the dispensing method. The issuance of a patent for these features would make illegal the unauthorized manufacture, use, sale and offer for sale of the protected packaging and cart features and unauthorized use of the dispensing method.

Call for more information
and pricing today.

