



# USP® SP PREFORMED PIPE BOOT

**Description:** USP® SP PREFORMED PIPE BOOTS are preformed flashings that can be cut to fit various pipe dimensions ranging from 1" to 4-1/2" in diameter. The USP® SP Preformed Pipe Boots are installed by the hot air welding procedure. All USP® SP Preformed Pipe Boots require metal clamps to be installed with an approved caulking applied.

**Use:** For use at pipe penetrations dimensions ranging from 1" to 4-1/2" in diameter.

**Application Guidelines:** USP® SP Preformed Pipe Boots are applied using hot air welding procedures. For use with USP® EV-PLUS, USP® FB EV-PLUS and USP® PVC Thermoplastic membranes.

**Product Data: USP® SP Preformed Pipe Boots (typical)**

Color: White

Thickness: .125"

Breaking Strength, psi, (MD/XD): 2,500 psi (D638)

Elongation at Break, (%), (MD/XD): 300% (D638)

Heat Aging (retained values): 90% (D638)

Vapor Permeability, g/m<sup>2</sup>/day: 2.8 (E96)

Low Temperature Flexibility, max, °F (°C): Pass @ -40°F (-40°C) (D2136)

Dimensional Change, %, max: <0.5% (D1204)

Accelerated Weathering, 10M Hrs: Pass (Zenon Arc)

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Elvaloy® is a registered trademark of DuPont.

Product Name <b>USP® SP Preformed Pipe Boots</b>	Item Code	Dimensions	
		Dia	Ht
USP® SP Preformed Pipe Boots	SP-BOOT-4- 1/2-7	4-1/2"	7"

**Approvals:** USP® SP Preformed Pipe Boots are Elvaloy® based (KEE) membranes and meets or exceeds the requirements of ASTM D4434 Standard Specification for polyvinyl chloride (PVC) based sheet roofing.



**CORPORATE HEADQUARTERS: P.O. BOX 11740, FORT WORTH,  
TEXAS 76110**

**TOLL-FREE: 866-PUSH-PLY (866) 787-4759  
LOCAL: (817) 413-0103 • FAX: (817) 413-8221  
[WWW.USPLY.COM](http://WWW.USPLY.COM)**