



DuraFlex® 190FR SBS

PRODUCT DATA SHEET

DuraFlex® 190FR SBS is a fire-resistant, granule surfaced, premium SBS (Styrene-Butadiene-Styrene) mop or cold adhesive applied membrane. Manufactured with a non-woven polyester mat and fiberglass strands for enhanced dimensional stability, high tear strength and puncture resistance. It is saturated and coated with high quality, asphaltic bitumen and SBS elastomers for a durable, flexible and easily maintainable membrane. Designed for use as a cap sheet in modified bitumen roof systems.

Physical Properties (ASTM D5147):	Test Results	ASTM D6164 Minimum Standard
Tensile Strength (lb/in), 0°F (MD/XMD)	135/120 lb/in	70 lb/in
Tensile Strength (lb/in), 73°F (MD/XMD)	98/89 lb/in	50 lb/in
Elongation (% @ Max Load), 0°F, (MD/XMD)	49/48 %	20%
Elongation (% @ Max Load), 73°F (MD/XMD)	54/60 %	35%
Elongation (% @ 5% Max Load), 73°F (MD/XMD)	62/68 %	38%
Tear Strength (lb), (MD/XMD), 73°F, minimum	129/117 lbf	55 lbf
Low Temperature Flexibility, (°F), maximum	0°F (-18°C)	0°F
Dimensional Stability, %, maximum	<0.2%	1%
High Temperature Stability, (°F)	250°F (121°C)	215°F
Granule Embedment, g/m ² avg. loss	1.9	<2 g

Product Data: DuraFlex® 190FR SBS (typical)

Thickness: 3.8mm (150 mils)


Weight: 105 lbs/roll (48 kg/m²)

Roll Dimensions: 39 3/8" x 32' 9" (1m x 10m)

Each roll is approximately 1 square

Green Standards Information: DuraFlex® 190FR SBS contains approximately 8.8% of recycled materials by product weight. 2.4% of materials are comprised of post-consumer recycled materials and 6.4% of materials are comprised of pre-consumer recycled materials. The post-consumer recycled materials are derived from recycled post-consumer plastics which averts disposal in landfills or commercial dumps. The pre-consumer recycled materials are derived from reclaimed non-hazardous coal combustion by-product waste which averts disposal of coal by-product waste in landfills or commercial dumps.

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Product Name: DuraFlex® 190FR SBS

Classification: Meets ASTM D 6164 Type I, Grade G. SBS Modified Bitumen Base Sheet

Application Method: Applied using compatible hot asphalt or SBS cold adhesive

Approvals: UL Classified with Underwriter's Laboratories (UL), is Factory Mutual (FM) Approved, and listed with Florida Building Code (FBC) FL-8077, and Texas Department of Insurance (TDI) RC-123. Contact U.S. Ply, Inc. for specific/applicable codes.



PROUDLY
MADE IN THE U.S.A.
BY U.S. PLY, INC.

CORPORATE HEADQUARTERS: P.O. BOX 1182, BRIDGEPORT, TEXAS 76426

PHONE: (817)413-0103 FAX: (817)413-8221

REV MAY 2023

WWW.USPLY.COM